



MASON INDUSTRIES, Inc.

Manufacturers of Vibration Control Products

350 Rabro Drive 2101 W. Crescent Ave., Suite D
 Hauppauge, NY 11788 Anaheim, CA 92801
 631/348-0282 714/535-2727
 FAX 631/348-0279 FAX 714/535-5738
 Info@Mason-Ind.com Info@MasonAnaheim.com
 www.Mason-Ind.com

JOB NAME _____
 CUSTOMER _____
 CUSTOMER P.O. _____
 MASON M.I. _____
 DWG. NO. _____

ML
 NEOPRENE
 LEVELING AND
 SHOCK MOUNTS

CADMIUM PLATED
 LEVELING BOLT
 is easy to turn


LOCKING NUT secures mount
 to machine after leveling. Use
 washers over oversized holes.

BRIGHT SAFETY
 YELLOW STEEL
 HOUSING


HEIGHT
 may be
 increased
 5/8" (16mm)
 by turning
 Leveling
 Bolt

NON-SKID
 NEOPRENE
 CUSHION


BRAKES
 AND
 SHEARS



INJECTION
 MOLDING
 MACHINES




CUT OFF
 MACHINES




IRON WORKERS

HOUSING
 DIAMETER




UNADJUSTED



ADJUSTED

TYPE ML DIMENSIONS and LOAD RATINGS

Type & Size	Capacity Range (lbs)	Capacity Range (kgs)	Steel Top Diameter (in) (mm)	Height (in) (mm)	Leveling Bolt	Bolt Length (in) (mm)
ML-3	100-500	46-226	3 1/2 90	1 1/8 28	1/2"-13	3 1/2 90
ML-5	500-1000	226-453	5 125	1 3/4 45	1/2"-13	5 125
ML-6	1000-4000	453-1814	6 1/4 160	1 3/4 45	3/4"-10	5 125
ML-8	4000-12000	1814-5443	8 200	2 50	1"-8	8 200



LATHES

PLAN VIEW OF MOUNT LOCATIONS

TAG : _____

UNIT : _____



SPECIFIED DEFLECTION

1 :	6 :
2 :	7 :
3 :	8 :
4 :	9 :
5 :	10 :

Material for One Set:

Sets Required: